

# CSIT115 Data Management and Security

## CSIT882 Data Management Systems

# SELECT statement (1)

Subject Coordinators: Dr Chen Chen, Dr Thanh Le

School of Computing and Information Technology -  
University of Wollongong

# SELECT statement (1)

## Outline

Functionality and syntax

Projection queries

Queries with row functions

Queries with group functions

Special queries

# Functionality and syntax

## Functionality

- **SELECT** statement retrieves data from a relational database
- The results of **SELECT** statement can be considered as a transient relational table
- The results of **SELECT** statement can be saved as a persistent relational table

In HTML view press 'p' to see the lecture notes

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

3/25


# Functionality and syntax

**Selection queries** select complete rows from a relational table

```
SELECT *
FROM ...
WHERE Condition ;
```

TABLE\_NAME

COLUMN_1	COLUMN_2	...	COLUMN_N
		...	
		...	
		...	



TABLE\_NAME

RESULTS

COLUMN_1	COLUMN_2	...	COLUMN_N
		...	
		...	

In HTML view press 'p' to see the lecture notes


[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

4/25

# Functionality and syntax

**Projection queries** select complete columns from a relational table



In HTML view press 'p' to see the lecture notes  
[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

5/25

# Functionality and syntax

## Sample database

```
CREATE TABLE DEPARTMENT(  
  name          VARCHAR(50)          NOT NULL,  
  code          CHAR(5)              NOT NULL,  
  total_staff_number DECIMAL(2)      NOT NULL,  
  chair         VARCHAR(50)          NULL,  
  budget        DECIMAL(9,1)         NULL, /* In this presentation */  
  CONSTRAINT dept_pkey PRIMARY KEY(name),    /* budget can be NULL */  
  CONSTRAINT dept_cke1 UNIQUE(code),  
  CONSTRAINT dept_cke2 UNIQUE(chair),  
  CONSTRAINT dept_cke3 CHECK (total_staff_number BETWEEN 1 AND 50) );
```

CREATE TABLE statement

```
CREATE TABLE COURSE(  
  cnum          CHAR(7)              NOT NULL,  
  title         VARCHAR(200)         NOT NULL,  
  credits       DECIMAL(2)           NOT NULL,  
  offered_by    VARCHAR(50)          NULL,  
  CONSTRAINT course_pkey PRIMARY KEY(cnum),  
  CONSTRAINT course_cke1 CHECK (credits IN (6, 12)),  
  CONSTRAINT course_fke1 FOREIGN KEY(offered_by)  
    REFERENCES DEPARTMENT(name) ON DELETE CASCADE );
```

CREATE TABLE statement

In HTML view press 'p' to see the lecture notes

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

6/25

# Functionality and syntax

## Examples

- Find a name and code of a department that has more than 30 staff members

```
SELECT code, name
FROM DEPARTMENT
WHERE total_staff_number > 30;
```

SELECT statement

- Find a code of a department and course number such that a course is offered by a department and a course provides 6 credit points

```
SELECT DEPARTMENT.code, COURSE.cnum, title
FROM DEPARTMENT JOIN COURSE
      ON DEPARTMENT.name = COURSE.offered_by
WHERE credits = 6;
```

SELECT statement with JOIN operation

- Find all information about courses offered by a department whose chair is James Bond

```
SELECT *
FROM COURSE
WHERE offered_by IN ( SELECT name
                      FROM DEPARTMENT
                      WHERE chair = 'James Bond' );
```

Nested SELECT statement

In HTML view press 'p' to see the lecture notes

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

7/25

# Functionality and syntax

## Examples

- Find all information about courses offered by a department whose chair is James Bond

```
SELECT COURSE.*  
FROM COURSE JOIN ( SELECT name  
                   FROM DEPARTMENT  
                   WHERE chair = 'James Bond' ) JB  
ON COURSE.offered_by = JB.name;
```

SELECT statement with inline view

- Find all information about courses offered by a department whose chair is James Bond

```
WITH JAMES AS  
  ( SELECT name  
    FROM DEPARTMENT  
    WHERE chair = 'James Bond' ),  
JAMESCOURSE AS  
  ( SELECT *  
    FROM COURSE JOIN JAMES  
    ON COURSE.offered_by = JAMES.name )  
SELECT JAMESCOURSE.* FROM JAMESCOURSE;
```

SELECT statement with WITH clause

In HTML view press 'p' to see the lecture notes

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

8/25



# Functionality and syntax

## Keywords

```
SELECT code, name
FROM DEPARTMENT
WHERE total_staff_number > 30;
```

SELECT statement

```
SELECT code, cnum, title
FROM DEPARTMENT, COURSE
WHERE name = offered_by AND credits = 6;
```

SELECT statement

```
SELECT *
FROM COURSE
WHERE offered_by IN ( SELECT name
                      FROM DEPARTMENT
                      WHERE chair = 'James Bond' );
```

Nested SELECT statement

```
SELECT COURSE.*
FROM COURSE JOIN ( SELECT name
                   FROM DEPARTMENT
                   WHERE chair = 'James Bond' ) JB
ON COURSE.offered_by = JB.name;
```

SELECT statement with inline view

In HTML view press 'p' to see the lecture notes

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

9/25

# Functionality and syntax

## Selected columns

```
SELECT code, name
FROM DEPARTMENT
WHERE total_staff_number > 30;
```

SELECT statement

```
SELECT code, cnum, title
FROM DEPARTMENT, COURSE
WHERE name = offered_by AND credits = 6;
```

SELECT statement

```
SELECT *
FROM COURSE
WHERE offered_by IN ( SELECT name
                      FROM DEPARTMENT
                      WHERE chair = 'James Bond' );
```

Nested SELECT statement

```
SELECT COURSE.*
FROM COURSE JOIN ( SELECT name
                   FROM DEPARTMENT
                   WHERE chair = 'James Bond' ) JB
ON COURSE.offered_by = JB.name;
```

SELECT statement with inline view

In HTML view press 'p' to see the lecture notes

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

10/25

# Functionality and syntax

## Relational tables used

```
SELECT code, name
FROM DEPARTMENT
WHERE total_staff_number > 30;
```

SELECT statement

```
SELECT code, cnum, title
FROM DEPARTMENT, COURSE
WHERE name = offered_by AND credits = 6;
```

SELECT statement

```
SELECT *
FROM COURSE
WHERE offered_by IN ( SELECT name
                      FROM DEPARTMENT
                      WHERE chair = 'James Bond' );
```

Nested SELECT statement

```
SELECT COURSE.*
FROM COURSE JOIN ( SELECT name
                   FROM DEPARTMENT
                   WHERE chair = 'James Bond' ) JB
ON COURSE.offered_by = JB.name;
```

SELECT statement with inline view

In HTML view press 'p' to see the lecture notes

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

11/25

# Functionality and syntax

## Conditions

```
SELECT code, name
FROM DEPARTMENT
WHERE total_staff_number > 30;
```

SELECT statement

```
SELECT code, cnum, title
FROM DEPARTMENT, COURSE
WHERE name = offered_by AND credits = 6;
```

SELECT statement

```
SELECT *
FROM COURSE
WHERE offered_by IN ( SELECT name
                      FROM DEPARTMENT
                      WHERE chair = 'James Bond' );
```

Nested SELECT statement

```
SELECT COURSE.*
FROM COURSE JOIN ( SELECT name
                   FROM DEPARTMENT
                   WHERE chair = 'James Bond' ) JB
ON COURSE.offered_by = JB.name;
```

SELECT statement with inline view

In HTML view press 'p' to see the lecture notes

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

12/25

# Functionality and syntax

## Subqueries

```
SELECT *  
FROM COURSE  
WHERE offered_by IN ( SELECT name  
                      FROM DEPARTMENT  
                      WHERE chair = 'James Bond' );
```

Nested SELECT statement

```
SELECT COURSE.*  
FROM COURSE JOIN ( SELECT name  
                  FROM DEPARTMENT  
                  WHERE chair = 'James Bond' ) JB  
ON COURSE.offered_by = JB.name;
```

SELECT statement with inline view

In HTML view press 'p' to see the lecture notes

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

13/25

# Functionality and syntax

## WITH clause

```
WITH JAMES AS
    ( SELECT name
      FROM DEPARTMENT
      WHERE chair = 'James Bond' ),
  JAMESCOURSE AS
    ( SELECT *
      FROM COURSE JOIN JAMES
      ON COURSE.offered_by = JAMES.name )
SELECT JAMESCOURSE.*
FROM JAMESCOURSE;
```

Nested SELECT statement

In HTML view press 'p' to see the lecture notes

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

14/25

# SELECT statement (1)

## Outline

Functionality and syntax

Projection queries

Queries with row functions

Queries with group functions

Special queries

# Projection queries

Projection queries select the entire columns from a relational table and do not have **WHERE** clause

Find full information about all departments

```
SELECT code, name, total_staff_number, chair, budget  
FROM DEPARTMENT;
```

[sql](#)

```
SELECT *  
FROM DEPARTMENT;
```

[sql](#)

Find the names and chairpersons of all departments

```
SELECT name, chair  
FROM DEPARTMENT;
```

[sql](#)

Find the titles of all courses

```
SELECT title  
FROM COURSE;
```

[sql](#)

[In HTML view press 'p' to see the lecture notes](#)

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

16/25



# Projection queries with duplicates/ no duplicates

A keyword **DISTINCT** can be used to eliminated duplicates from the results of a query

Find the credit points of all courses

```
SELECT credits  
FROM COURSE;
```

[sql](#)

Find the distinct credit points of all courses

```
SELECT DISTINCT credits  
FROM COURSE;
```

[sql](#)

Find the distinct total number of staff members in each department

```
SELECT DISTINCT total_staff_number  
FROM DEPARTMENT;
```

[sql](#)

[In HTML view press 'p' to see the lecture notes](#)

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

17/25

# SELECT statement (1)

## Outline

Functionality and syntax

Projection queries

Queries with row functions

Queries with group functions

Special queries

# Queries with row functions

A **row function** is called and it is processed one time for each row selected from a relational table

List the names of departments in uppercase format

```
SELECT UPPER(name)
FROM DEPARTMENT;
```

UPPER row function

Find the first three characters from all course codes and full titles of all courses

```
SELECT SUBSTR(cnum, 1, 3), title
FROM COURSE;
```

SUBSTR row function

Display the name of departments and budgets increased by 10%

```
SELECT name, 1.1*IFNULL(budget,0)
FROM DEPARTMENT;
```

IFNULL row function

[In HTML view press 'p' to see the lecture notes](#)

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

19/25

# SELECT statement (1)

## Outline

Functionality and syntax

Projection queries

Queries with row functions

Queries with group functions

Special queries

In HTML view press 'p' to see the lecture notes

TOP

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

20/25

# Queries with group functions

A **group function** is called and it is processed one time for a group of rows

Find the total number of courses

```
SELECT COUNT(*)  
FROM COURSE;
```

COUNT group function

Find the total number of all staff members in all departments

```
SELECT SUM(total_staff_number)  
FROM DEPARTMENT;
```

SUM group function

Find an average budget per each department

```
SELECT AVG(IFNULL(budget, 0))  
FROM DEPARTMENT;
```

AVG group function

Find the total number of staff members in the largest department

```
SELECT MAX(total_staff_number)  
FROM DEPARTMENT;
```

MAX group function

[In HTML view press 'p' to see the lecture notes](#)

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

21/25

# SELECT statement (1)

## Outline

Functionality and syntax

Projection queries

Queries with row functions

Queries with group functions

Special queries

# Special queries

SQL as a calculator

Compute 30 hours \* \$90.30 per hour

```
SELECT 30 * 90.30  
FROM DUAL;
```

Arithmetic expression in SELECT clause

SQL as a diary

What date is tomorrow ?

```
SELECT DATE_ADD(SYSDATE(), INTERVAL 1 DAY)  
FROM DUAL;
```

Date arithmetic

Add 2 months to a current date

```
SELECT DATE_ADD(SYSDATE(), INTERVAL 2 MONTH )  
FROM DUAL;
```

Date arithmetic

In HTML view press 'p' to see the lecture notes

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

23/25

# Special queries

How many days have passed since 1 January 2001 ?

```
SELECT DATEDIFF(SYSDATE(), '2001-01-01')  
FROM DUAL;
```

Date arithmetic

SQL as word processor

Who am I ?

```
SELECT CONCAT('I am ', CURRENT_USER())  
FROM DUAL;
```

String concatenation and user name

Hello world !

```
SELECT 'Hello world !'  
FROM DUAL;
```

The famous Hello world ! program

Substring of 'Hello world' that starts from the first 'e'

```
SELECT SUBSTR('Hello world', INSTR('Hello world', 'e'), LENGTH('Hello world'))  
FROM DUAL;
```

String processing

In HTML view press 'p' to see the lecture notes

[TOP](#)

Created by Janusz R. Getta, CSIT115 Data Management and Security, Autumn 2023

24/25



# References

C. Coronel, S. Morris, A. Basta, M. Zgola, Data Management and Security, Chapter 5 Introduction to Structured Query Language, Cengage Compose eBook, 2018, [eBook: Data Management and Security, 1st Edition](#)

T. Connolly, C. Begg, Database Systems, A Practical Approach to Design, Implementation, and Management, Chapters 6.3.1 - 6.3.4 Data Manipulation, Pearson Education Ltd, 2015

D. Darmawikarta, SQL for MySQL A Beginner's Tutorial, Chapters 2 - 5, Brainy Software Inc. First Edition: June 2014

[How to ... ? Cookbook, How to implement queries in SQL, Recipe 5.1 How to implement SELECT statements with simple Boolean expressions ?](#)