

CSIT115 Data Management and Security

CSIT882 Data Management Systems

The Relational Model of Data

Subject coordinators: Dr Chen Chen, Dr Thanh Le Hoang

Slides created by Dr Janusz R. Getta, School of Computing and Information Technology -
University of Wollongong

The Relational Model of Data

Outline

Basic Concepts

Relational Table

Principles of Relational Model

Consistency Constraints

Summary

Basic Concepts

Data model ? What is it ?

A **data model** provides an abstract view of data that can be used for data definition, data manipulation, data retrieval, and data administration

Accordingly to [Wikipedia](#)) a **data model** organises data elements and standardises how the data elements relate to one another

Because a **data model** provides an abstract view it is also commonly called as a **view of data**, e.g. classes, associations, two dimensional tables

In 1970 **Edgar Frank Codd from IBM Corporation** defined a model of data based on a tabular view and called it as **Relational Model of Data** or simply **Relational Model**

At the moment (early 2024) ~95% of all database systems is based on **Relational Model of Data**

Basic Concepts

What view of data provides **Relational Model of Data** ?

- The model provide a **tabular view of data**
- A **relational table** consists of a **header** and theoretically an unlimited number of **rows**
- A **header** consists of a sequence of **attribute** names
- A **row** consists of a sequence of values of attributes
- A vertical sequence of **attribute name** followed by the **attribute values** is called a **column**
- A **header** is also called a **relational schema**
- A set of all values of an **attribute** is called a **domain** of an attribute
- A **database** is a set of **relational tables**

Relational Table

A sample relational table:

RELATIONAL TABLE							
	Column	Attribute name	Attribute value	Missing value			
Header	anum	fname	lname	dob	city	state	phone
Row	1	Harry	Potter	1980-12-12	Perth	Western Australia	645278453
	2	Johnny	Walker	1990-01-11	Geelong	Victoria	63569784
	3	Mary	Poppins	1950-01-01	Melbourne	Victoria	62389541
	4	Michael	Collins	1960-05-25	Brisbane	Queensland	63336666
	5	Margaret	Finch	1953-12-07	Sydney	New South Wales	64573489
	6	Claudia	Kowalewski	1959-05-03	Hobart	Tasmania	64577744
	7	James	Bond	1960-01-01	Perth	Western Australia	645278434
	8	Stephen	Staunton	1977-10-23	Freemantle	Western Australia	NULL
	9	Joseph	Staunton	1977-10-23	Newcastle	New South Wales	623778453
	10	John	Spiderman	1990-06-21	Sydney	New South Wales	24256789
	11	George	TheFirst	1991-10-12	Melbourne	Victoria	NULL
	12	Homer	Simpson	1957-05-24	Adelaide	South Australia	61369876
	13	Neil	Superman	1960-07-20	Perth	Western Australia	45672345
	14	Ivan	TheTerrible	1969-05-11	Brisbane	Queensland	123567898
	15	Penelope	Princess	1977-10-23	Hobart	Tasmania	40076711
	16	Zhi Chao	Zhong	1971-07-21	Horsley	New South Wales	86150189
	17	Richard	TheLionheart	1981-06-02	Waga Waga	New South Wales	61234567
	18	Sherlock	Holmes	1935-06-13	Bundaberg	Queensland	46676601
	19	Robin	Hood	1951-08-21	Horsley	New South Wales	86150329
	20	Janusz	Getta	1953-10-03	Horsley	New South Wales	12345678

Relational Table

Why a **relational table** is called as a "**relational**" ?

This is because of the following original E.F. Codd's definition of a **relational table**:

- Let A_1, A_2, \dots, A_n be the names of attributes
- Let $\text{dom}(A_1), \text{dom}(A_2), \dots, \text{dom}(A_n)$ be the domains of the attributes, A_1, A_2, \dots, A_n , it means, the sets of values of each attribute A_1, A_2, \dots, A_n
- A **relational table** is defined as a subset of the **Cartesian Product** $\text{dom}(A_1) \times \text{dom}(A_2) \times \dots \times \text{dom}(A_n)$

In mathematics a subset of the **Cartesian Product** is known as a **relation**

This is why a relational table is called "**relational**"

The Relational Model of Data

Outline

Basic Concepts

Relational Table

Principles of Relational Model

Consistency Constraints

Summary

Principles of Relational Model

A relational table that has **no multivalued attributes and composite attributes** is in the **first normal form (1NF)**

For example, a relational table below is **NOT** in **1NF**

e#	name	car used
950001	Peter	Toyota, PKR234 Ford, WER545
932345	Paul	Honda, RTQ456
960020	Joan	Holden, KLR197 Holden, KLR567

Sometimes we say, that such table is in **0NF** or that it is a **nested table**

Are there any **higher normal forms** like for example **2NF, 3NF, ... ?**

YES ! However, we shall not discuss this topic now. It will be covered later in CSIT882 only.

Principles of Relational Model

Access to the rows by the contents rule:

- We can only retrieve rows by their contents

It is NOT allowed to say: give me the second row from the following table:

APPLICANT Table

anum	fname	lname	dob	city	state
1	Harry	Potter	1980-12-12	Perth	Western Australia
2	Johnny	Walker	1990-01-13	Geelong	Victoria
3	Mary	Poppins	1950-01-01	Melbourne	Victoria
4	Michael	Collins	1960-05-25	Brisbane	Queensland
5	Margaret	Finch	1953-12-07	Sydney	New South Wales
6	Claudia	Kowalewski	1959-05-03	Hobart	Tasmania
7	James	Bond	1960-01-01	Perth	Western Australia
8	Stephen	Staunton	1977-10-23	Freemantle	Western Australia
9	Joseph	Staunton	1977-10-23	Newcastle	New South Wales
10	John	Spiderman	1990-06-21	Sydney	New South Wales

We have to say: give me a row such that `anum = 2` or such that `fname = 'Johnny' and lname = 'Walker'`

Principles of Relational Model

Unique rows rule:

- A relational table cannot contain two identical rows

This rule is violated by all commercial Database Management Systems !

The Relational Model of Data

Outline

Basic Concepts

Relational Table

Principles of Relational Model

Consistency Constraints

Keys

NULL

Referential Integrity Constraints

Domain Constraints

Summary

Keys

Let $R(A_1, A_2, \dots, A_n)$ be a relational table with a relational schema (header) $\{A_1, A_2, \dots, A_n\}$

A **key** for a table R is a set of attributes $K = \{A_{k1}, A_{k2}, \dots, A_{km}\}$ such that:

- (1) K is included in $\{A_1, A_2, \dots, A_n\}$, it means, that K is a subset of the relational schema $\{A_1, A_2, \dots, A_n\}$
- (2) for any two rows v, w in $R(A_1, A_2, \dots, A_n)$ their k -values must be different, i.e. $v[k] \neq w[k]$
- (3) no proper subset of K satisfies a property (2) above

A **key** that does not satisfy a condition (3) is called as **superkey**

A **key** that satisfies the conditions (1) and (2) and (3) is called as **minimal key**

Keys

Examples:

- A set of attributes {snum} is a **minimal key** in a relational schema
STUDENT={snum, first-name, last-name, date-of-birth}
- A set of attributes {snum, last-name} is a **superkey** in a relational schema
STUDENT={snum, first-name, last-name, date-of-birth}
- A set of attributes {bldg#, room#} is a **minimal key** in a relational schema
ROOM={bldg#, room#, area}
- A set of attributes {p#, manufacturer, price} is a **superkey** in a relational schema
PART={p#, name, price, manufacturer}
- A set of attributes {p#, manufacturer} is a **superkey** in a relational schema
PART={p#, name, price, manufacturer}
- A set of attributes {p#} is a **minimal key** in a relational schema
PART={p# name, price, manufacturer}

Keys

More examples:

- A set of attributes {pnum, first-name, last-name, dob, team} is a **superkey** in a relational schema
PLAYER={pnum, first-name, last-name, dob, team}
- A set of attributes {pnum, first-name, last-name, dob} is a **superkey** in a relational schema
PLAYER={pnum, first-name, last-name, dob, team}
- A set of attributes {first-name, last-name, dob} is a **minimal key** in a relational schema
PLAYER={pnum, first-name, last-name, dob, team}
- A set of attributes {supplier-num, part-num, delivery-date, delivery-address} is a **minimal key** in a relational schema
SHIPMENT={supplier-num, part-num, delivery-date, delivery-address}

Keys

All **minimal keys** valid in a relational schema are also called as **candidate keys**

A **primary key** is one of the **candidate keys** arbitrarily chosen by a database designer to uniquely identify the rows in a relational table

Examples:

- A set of attributes **{snum}** and a set of attributes **{first-name, last-name, date-of-birth}** are the **candidate keys** in a relational schema **STUDENT={snum, first-name, last-name, date-of-birth}**
- A **candidate key {snum}** can be selected by a database designer as a **primary key**
- It is also possible that a **candidate key {first-name, last-name, date-of-birth}** can be selected by a database designer as a **primary key**

In the future a relational schema $R = \{A_1, A_2, \dots A_n\}$ will be denoted by $R(A_1, A_2, \dots A_n)$ and any sort of key $\{A_{i1}, A_{i2}, \dots A_{im}\}$ included in R will be denoted by $(A_{i1}, A_{i2}, \dots A_{im})$

The Relational Model of Data

Outline

Basic Concepts

Relational Table

Principles of Relational Model

Consistency Constraints

Keys

NULL


Referential Integrity Constraints

Domain Constraints

Summary

NULL

A **NULL** constraint says that an attribute in a relational table may have no values at all



With an exception saying that no column belonging to a primary key or candidate key is allowed to take on **NULL** for any row (it is also called as Entity Integrity constraint)

The Relational Model of Data

Outline

Basic Concepts

Relational Table

Principles of Relational Model

Consistency Constraints

Keys

NULL


Referential Integrity Constraints

Domain Constraints


Summary

Referential Integrity Constraints

A set of attributes F in a relational schema R is called a **foreign key** if the combination of values of attributes in F in any row is required to either contain **NULL**s or else to match the value combination of a set of columns P representing a candidate or primary key in some other relational schema S



Referential Integrity Constraints



A **referential integrity rule** is in force if the columns of a foreign key in any relational table either:

- (1) have **NULLs** in at least one column that allows **NULLs**
- (2) have no **NULLs** and a combination of all its values is equal to the combination of primary key values in the other relational table

Referential Integrity Constraints

Example of **referential integrity constraint**:

- A relational schema `BUILDING(bldg#, floor#, name)` has a **primary key (bldg#)**
- A relational schema `ROOM(bldg#, room#, area)` has a **primary key (bldg#, room#)**
- Then a set of attributes `(bldg#)` included in a schema `ROOM` is a **foreign key** that references a **primary key (bldg#)** in a schema `BUILDING`

Another example of **referential integrity constraint**:

- A relational schema `STUDENT(s#, first-name, last-name, dob)` has a **primary key (s#)**
- A relational schema `SUBJECT(code, title, credits)` has a **primary key (code)**
- Then a relational schema `ENROLMENT(s#, code, edate)` has a foreign key `(s#)` referencing **primary key {s#}** in a schema `STUDENT` and ...
- ... a relational schema `ENROLMENT(s#, code, edate)` has a **foreign key (code)** referencing **primary key (code)** in a schema `SUBJECT`

Referential Integrity Constraints

Yet another example of **referential integrity constraint**:

- A relational schema **ROOM**=(bldg#, room#, area) has a **primary key** (bldg#, room#)
- A relational schema **LECTURER**=(emp#, first-name, last-name, bldg#, room#) has a **primary key** (emp#)
- Then a set of attributes (bldg#, room#) included in a relational schema **LECTURER** is a **foreign key** that references a **primary key** (bldg#, room#) in a schema **ROOM**

The Relational Model of Data

Outline

Basic Concepts

Relational Table

Principles of Relational Model

Consistency Constraints

Keys

NULL

Referential Integrity Constraints

Domain Constraints

Summary

Domain Constraints

A **domain constraint** is a condition imposed on the values of an attribute **A** that determines the values of $\text{dom}(A)$, i.e. a **domain** of attribute **A**.

Examples:

- An attribute **student-number** is a sequence of 7 digits
- An attribute **date-of-birth** cannot have a value greater than today's date
- An attribute **salary** is a positive real number
- A value of an attribute **credits** can be either 6 or 12
- A value of an attribute **first-name** is a string of letters and blanks that starts from a capital letter

The Relational Model of Data

Outline

Basic Concepts

Relational Table

Principles of Relational Model

Consistency Constraints

Summary

Summary

A **database** is a collection of **relational tables**

A **relational table** consists of **rows** (**tuples**) and **columns** (**attributes**)

All **attributes** have **atomic values**

Each **attribute** has a **domain**, it means, that a set of acceptable values

A **relational table** is a **subset** of the **Cartesian Product** of **attribute domains**

An **attribute** may have no value (**NULL**)

A **relational table** implements either a **class of objects** or an **association**

All **identifiers** in a **conceptual schema** are implemented as the **keys** in the **relational tables**

Summary

A "tourist guide" through a "land of keys"

- Minimal key => the smallest key
- Superkey => minimal key + other attribute(s)
- Candidate key => any minimal key
- Primary key => one of candidate keys
- Foreign key => an attribute or set of attributes referencing a primary key or a candidate key in another or the same relational table

References

C. Coronel, S. Morris, A. Basta, M. Zgola, Data Management and Security, Chapter 2 Cengage Compose eBook, 2018, eBook: Data Management and Security, 1st Edition

T. Connolly, C. Begg, Database Systems, A Practical Approach to Design, Implementation, and Management, Chapter 4 The Relational Model, Pearson Education Ltd, 2015