

# CSIT884: Web Development

## Document Object Model - DOM

School of Computing and Information  
Technology  
University of Wollongong



UNIVERSITY  
OF WOLLONGONG  
AUSTRALIA

# **Objectives:**

- Understand Document Object Model of a website
- Use JavaScript to generate dynamic content on a website


# DOM

Document Object Model (DOM):

- represents the structure of a webpage as a tree in memory
- allows access to the tree via programming language such as JavaScript

We can use JavaScript to change structure, style and content of a website via its DOM.

# DOM tree



# Manipulate DOM tree

We can use DOM to create dynamic web page:

- add new HTML elements and attributes
- change HTML elements
- change HTML attributes
- change CSS styles
- remove existing HTML elements and attributes
- create new HTML events

The document object represents a website.

- Select an element by id:

```
document.getElementById(id)
```

- Select elements by tag name:

```
document.getElementsByTagName(tagName)
```

- Select elements by class name:

```
document.getElementsByClassName(className)
```

# Create an element

```
var element = document.createElement(tagName);
```

- **tagName is a string specifying the type of element to be created, such as h1, li, p, button, div, span, ...**
- **element is the constructed element**

## Example:

```
var h1 = document.createElement("h1");
```

```
var para = document.createElement("p");
```

```
var span = document.createElement("span");
```

# Create a text node

```
var textNode = document.createTextNode(data);
```

- `data` is a string containing the data to be put in a text node
- `textNode` is the constructed Text Node

After a Text Node is created, we can insert it into an element on the web page by calling:

```
element.appendChild(textNode)
```

```
element.insertBefore(textNode, existingChild)
```

# Delete/change an element

- Remove an HTML element:

```
document.removeChild(element);
```

- Replace an HTML element:

```
document.replaceChild(new, old);
```

# Manipulating element's attributes

- Accessing an attribute value

```
element.getAttribute(attrName) ;
```

```
element.setAttribute(attrName, attrValue) ;
```

# Example: add dependant

Let the user enter dependants information and display them in an **unordered list**.

First name:	Mary
Last name:	Smith
Relationship:	daughter

Add dependant

- John Smith, son
- Mary Smith, daughter

# Example: add dependant

```
<input type="text" id="firstNameInput" />  
<input type="text" id="lastNameInput" />  
<input type="text" id="relationInput" />  
  
<button onClick="addDependant () ">Add dependant</button>
```

```
<ul id="personList">  
</ul>
```

First name:

Last name:


Relationship:

Add dependant

- John Smith, son
- Mary Smith, daughter

# Example: add dependant

DOM tree:



```
<ul id="personList">  
</ul>
```

- John Smith, son
- Mary Smith, daughter

# Example: add dependant

```
function addDependant() {  
    // get person info  
    // create a new list item holding the person info  
    // add the new list item element to the unordered list  
}
```

First name:	Mary
Last name:	Smith
Relationship:	daughter

Add dependant

- John Smith, son
- Mary Smith, daughter

# Example: add dependant

```
function addDependant () {  
    // get person info  
    var firstNameTf = document.getElementById("firstNameInput");  
    var firstName = firstNameTf.value;  
  
    var lastNameTf = document.getElementById("lastNameInput");  
    var lastName = lastNameTf.value;  
  
    var relationTf = document.getElementById("relationInput");  
    var relation = relationTf.value;  
  
    var personInfo = firstName + " " + lastName + ", " + relation;
```

First name:	Mary
Last name:	Smith
Relationship:	daughter

Add dependant

- John Smith, son
- Mary Smith, daughter

# Example: add dependant

```
function addDependant() {  
    // get person info  
    ...  
    var personInfo = firstName + " " + lastName + ", " + relation;  
  
    // create a new list item holding the person info  
    var li = document.createElement("li");  
    var personText = document.createTextNode(personInfo);  
    li.appendChild(personText);  
  
    // add the new list item element to the unordered list  
    var personUL = document.getElementById("personList");  
    personUL.appendChild(li);  
}
```

First name:	Mary
Last name:	Smith
Relationship:	daughter

Add dependant

- John Smith, son
- Mary Smith, daughter

# Example: add dynamic elements

Let the user enter HTML tag name and some text, then create an element with the specified tag name holding the text, and display the created element on the webpage.

Enter HTML tag:

Enter some text:

**Add element**

# Wollongong

city of innovation

Hi there

# Example: add dynamic elements

```
<input type="text" id="tagInput" />  
<input type="text" id="textInput" />  
<button onClick="addElement()">Add element</button>  
  
<div id="elementHolder">  
</div>
```

Enter HTML tag:

Enter some text:


**Wollongong**

city of innovation

Hi there

# Example: add dynamic elements

DOM tree:



Enter HTML tag:

Enter some text:

**Add element**

# Wollongong

```
<div id="elementHolder">  
/</div>
```

city of innovation

Hi there

# Example: add dynamic elements

```
function addElement() {  
    // get tag name and text from user  
    // create a new element holding the text  
    // add the new element to the div  
}
```

Enter HTML tag:

Enter some text:

**Wollongong**

city of innovation

Hi there

# Example: add dynamic elements

```
function addElement() {  
    // get tag name and text from user  
    var tagTf = document.getElementById("tagInput");  
    var tag = tagTf.value;  
  
    var textTf = document.getElementById("textInput");  
    var text = textTf.value;
```

Enter HTML tag:

Enter some text:

**Wollongong**

city of innovation

Hi there

# Example: add dynamic elements

```
function addElement() {  
    // get tag name and text from user  
  
    ...  
  
    // create a new element holding the text  
  
    var element = document.createElement(tag);  
  
    var textNode = document.createTextNode(text);  
  
    element.appendChild(textNode);
```

Enter HTML tag:

Enter some text:

**Add element**

# Wollongong

city of innovation

Hi there

# Example: add dynamic elements

```
function addElement() {  
    // get tag name and text from user  
    ...  
    // create a new element holding the text  
    ...  
    // add the new element to the div  
    var holderDiv = document.getElementById("elementHolder");  
    holderDiv.appendChild(element);  
}
```

Enter HTML tag:

Enter some text:

**Wollongong**

city of innovation

Hi there

# References

- Jennifer Niederst Robbins, Learning Web Design - A Beginner's guide to HTML, CSS, JavaScript and Web Graphics, 5th edition, O'Reilly Media, 2018.
- Eric T. Freeman and Elisabeth Robson, Head First JavaScript Programming, O'Reilly Media, 2014.
- <http://www.w3schools.com/js>
- <http://developer.mozilla.org/en-US/docs/Web/JavaScript>
- [https://developer.mozilla.org/en-US/docs/Web/API/Document\\_Object\\_Model](https://developer.mozilla.org/en-US/docs/Web/API/Document_Object_Model)